


**SPEED - TORQUE & CURRENT CURVE**

Curve No.

1ST\_D1ML20834

OUTPUT	150 kW	POLES	4 P
VOLTAGE	- V	FREQUENCY	60 Hz
FULL LOAD TORQUE	81.6 kg·m	FULL LOAD CURRENT	- A
LOCKED ROTOR TORQUE	100 %	LOCKED-ROTOR CURRENT	750 %
BREAKDOWN TORQUE	240 %	SPEED (at FULL LOAD)	1790 r/min
GD <sup>2</sup> of LOAD :	- kg·m <sup>2</sup>	GD <sup>2</sup> of MOTOR	15.963 kg·m <sup>2</sup>




**NOTE**

- A : SPEED-TORQUE CURVE AT 100% RATED VOLTAGE
- ▲— B : SPEED-TORQUE CURVE AT 90% RATED VOLTAGE
- C : SPEED-TORQUE CURVE AT 80% RATED VOLTAGE
- - - D : SPEED-CURRENT CURVE AT 100% RATED VOLTAGE
- - - E : SPEED-CURRENT CURVE AT 90% RATED VOLTAGE
- · · F : SPEED-CURRENT CURVE AT 80% RATED VOLTAGE

<b>HYOSUNG</b> HEAVY INDUSTRIES	<b>THERMAL LIMIT &amp; TIME - CURRENT CURVE</b>			<b>Curve No.</b>	
				1TL_D1ML20834	


OUTPUT	150 kW	POLES	4 P
VOLTAGE	- V	FREQUENCY	60 Hz
FULL LOAD TORQUE	81.6 kg·m	FULL LOAD CURRENT	- A
LOCKED ROTOR TORQUE	100 %	LOCKED-ROTOR CURRENT	750 %
BREAKDOWN TORQUE	240 %	SPEED (at FULL LOAD)	1790 r/min
GD <sup>2</sup> of LOAD :	- kg·m <sup>2</sup>	GD <sup>2</sup> of MOTOR	15.963 kg·m <sup>2</sup>



**NOTE**

- A : THERMAL LIMIT CURVE AT HOT CONDITION
- - - B : THERMAL LIMIT CURVE AT COLD CONDITION
- · — C ※TIME-CURRENT CURVES(C,D,E) NEED BELOW DATA TO BE DRAWN
- · - D \* LOAD GD<sup>2</sup> AT MOTOR SHAFT
- · · E \* SPEED-TORQUE CURVE OF LOAD

<b>HYOSUNG</b> HEAVY INDUSTRIES	<b>LOAD - POWER FACTOR &amp; EFFICIENCY CURVE</b>			<b>Curve No.</b>	
				1PE_D1ML20834	
OUTPUT	150	kW	POLES	4	P
VOLTAGE	-	V	FREQUENCY	60	Hz
FULL LOAD TORQUE	81.6	kg·m	FULL LOAD CURRENT	-	A
LOCKED ROTOR TORQUE	100	%	LOCKED-ROTOR CURRENT	750	%
BREAKDOWN TORQUE	240	%	SPEED (at FULL LOAD)	1790	r/min
GD <sup>2</sup> of LOAD :	-	kg·m <sup>2</sup>	GD <sup>2</sup> of MOTOR	15.963	kg·m <sup>2</sup>



**NOTE**

— A : LOAD - POWER FACTOR CURVE

- - - B : LOAD - EFFICIENCY CURVE