


SPEED - TORQUE & CURRENT CURVE

Curve No.
1ST_DSML20701M

OUTPUT	1.5 kW	POLES	4 P
VOLTAGE	- V	FREQUENCY	60 Hz
FULL LOAD TORQUE	0.8 kg·m	FULL LOAD CURRENT	- A
LOCKED ROTOR TORQUE	230 %	LOCKED-ROTOR CURRENT	740 %
BREAKDOWN TORQUE	280 %	SPEED (at FULL LOAD)	1750 r/min
GD ² of LOAD :	- kg·m ²	GD ² of MOTOR	0.024 kg·m ²




NOTE

- A : SPEED-TORQUE CURVE AT 100% RATED VOLTAGE
- ▲— B : SPEED-TORQUE CURVE AT 90% RATED VOLTAGE
- C : SPEED-TORQUE CURVE AT 80% RATED VOLTAGE
- - - D : SPEED-CURRENT CURVE AT 100% RATED VOLTAGE
- - - E : SPEED-CURRENT CURVE AT 90% RATED VOLTAGE
- . - F : SPEED-CURRENT CURVE AT 80% RATED VOLTAGE


	THERMAL LIMIT & TIME - CURRENT CURVE			Curve No.	
				1TL_DSML20701M	


OUTPUT	1.5 kW	POLES	4 P
VOLTAGE	- V	FREQUENCY	60 Hz
FULL LOAD TORQUE	0.8 kg·m	FULL LOAD CURRENT	- A
LOCKED ROTOR TORQUE	230 %	LOCKED-ROTOR CURRENT	740 %
BREAKDOWN TORQUE	280 %	SPEED (at FULL LOAD)	1750 r/min
GD ² of LOAD :	- kg·m ²	GD ² of MOTOR	0.024 kg·m ²



NOTE

- A : THERMAL LIMIT CURVE AT HOT CONDITION
- - - - - B : THERMAL LIMIT CURVE AT COLD CONDITION
- - - - - C ※TIME-CURRENT CURVES(C,D,E) NEED BELOW DATA TO BE DRAWN
- · - · - D * LOAD GD² AT MOTOR SHAFT
- · · · · E * SPEED-TORQUE CURVE OF LOAD

	LOAD - POWER FACTOR & EFFICIENCY CURVE		Curve No.	
			1PE_DSML20701M	
OUTPUT	1.5 kW	POLES	4	P
VOLTAGE	- V	FREQUENCY	60	Hz
FULL LOAD TORQUE	0.8 kg·m	FULL LOAD CURRENT	-	A
LOCKED ROTOR TORQUE	230 %	LOCKED-ROTOR CURRENT	740	%
BREAKDOWN TORQUE	280 %	SPEED (at FULL LOAD)	1750	r/min
GD ² of LOAD :	- kg·m ²	GD ² of MOTOR	0.024	kg·m ²



NOTE

A : LOAD - POWER FACTOR CURVE
 B : LOAD - EFFICIENCY CURVE